INSTALLATION INSTRUCTIONS

BULL BAR PART#82501.21/82001.21 2007 TOYOTA FJ CRUISER

PARTS LIST:

1 BULL BAR

2 BRACKETS DRIVER/ PASSENGER

4 7/16 X 1 1/4 HEX HEAD BOLTS

4 7/16 HEX NUTS

8 7/16 FLAT WASHERS


4 3/8 X 4 1/2 HEX HEAD BOLT

4 3/8 NYLOC HEX NUT

8 3/4 FLAT WASHERS


PROCEDURE:

- 1- REMOVE CONTENTS FROM BOX AND CHECK FOR DAMAGE. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY.
- 2- LOCATE FRAME MOUNT FOR LOWER BRACKET (DRIVER SIDE SHOWN). INSERT (2) 3/8 X 4 1/2 HEX HEAD BOLTS, (2) 3/8 FLAT WASHERS. INSTALL LOWER BRACKET USING (2) 3/8 HEX NYLOC NUTS, (2) 3/8 HEX NYLOC NUTS (2) 3/8 FLAT WASHERS, LEAVE LOOSE. SEE FIG. #1
- 3- REPEAT PROCEDURE #2 ON OPPOSITE SIDE
- 4- INSTALL BULL BAR ONTO VEHICLE USING (4) 7/16 X 1 1/4 HEX HEAD BOLTS, (4) 7/16 HEX NYLOC NUTS, (8) 7/16 FLAT WASHERS. LEAVE LOOSE SEE FIG #2.
- 5- LEVEL AND ADJUST BULL BAR AS DESIRED THEN TIGHTEN.



SHOWN

3/8 x 4 1/2 HARDWARE



PASSENGER SIDE SHOWN

7/16 HARDWARE