

INSTALLATION INSTRUCTIONS

07 SILVERADO 1500 BULL BAR
PART NUMBER 82501.07/82001.07

PARTS LIST:

1	Bull Bar	1	Drivers Side Bracket
1	Passenger Side Bracket	1	12-1.75X40mm Bolt plate
1	12mm washer	1	12mm lock Nut
4	8-1.25X30mm Bolt	4	8mm Lock Washers
4	8mm Flat Washers		

PROCEDURE:

1. REMOVE CONTENTS FROM BOX AND VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY. PLEASE NOTE THAT YOU CAN NOT USE FACTORY TOW HOOKS WITH THIS BULL BAR.
2. Locate and set aside the Bull Bar, hardware kit and the brackets. Determine the driver and passenger sides for the brackets. (Fig 1)
3. Remove the factory tow hooks and set aside the two long bolts and nuts. (Fig 1) You can not reinstall the tow hooks so put the two short bolts back into tow hooks and store away.
4. Take the driver's side mounting bracket and attach it to the driver's side of the bull bar as shown, (Fig 2) using two of the 8mm bolts, flat washers and lock washers. Repeat this step on the passenger's side, making sure to tighten down all four bolts.
5. Slide the bull bar onto the frame through the bumper openings. The brackets go on the outside of the frame tubes. On the drivers side replace the long stock tow hook bolt into the front hole and finger tighten the stock nut in place. (Fig 3)
6. On the passenger side of truck, bend the bumper opening tabs in and out of the way. Putting your hand through one of the skid plate slots, slide the 12mm bolt plate into the frame tube and through the rear tow hook mounting hole. Place the 12mm flat washer in place the finger tighten the Nylock nut. (Fig 4,5 & 6) Next replace the passenger side long tow hook bolt and nut.
7. Adjust the fit of bull bar to trucks bumper, to an even spacing top to bottom and tighten up the three bolts attaching it to the truck. (Fig 7)

Cleaning Instructions:

For stainless steel may be used to polish small scratches and scuffs on the finish. Mild soap, window or glass cleaner may be used to clean stainless steel.

For black powder coated finish. Mild soap, window and glass cleaner may be used. Do not use any type of polish or wax that contains abrasive that could damage the finish.



